Philips
Fiber optic cable

1,5 m

SWA6360

Enjoy the ultimate listening experience

with this fibre optic cable

Take your components to optimum performance. This top of the line speaker wire offers the best connection for transferring audio signals between components.

Enjoy better audio quality
- High quality digital cable for great signal transfer

Protects against signal loss
- 100% aluminum shielding
- Copper braided shielding
- Foam Polyethlene (FPE) Dielectric
- Oxygen-free copper conductor for ideal signal transfer

Easy installation
- Color coded connectors for instant recognition
- Non-slip ergonomic grip for easy use
- Plug and play for easy use

Enjoy extended durability
- Heavy-duty brass shell for extended durability
- Super pliable jackets for outstanding flexibility
- Reliable metal strain relief

PHILIPS
sense and simplicity

Fiber optic cable
1,5 m

SWA6360/93

Specifications

Packaging Data
- Quantity: 1
- EAN/UPC/GTIN: 87 10895 95422 8
- Gross weight: .21 kg
- Tare weight: .08 kg
- Net weight: .13 kg
- Length: 230 mm
- Width: 165 mm
- Height: 60 mm

Inner Carton
- EAN/UPC/GTIN: 87 10895 97658 9
- Quantity: 2
- Gross weight: .54 kg
- Tare weight: .28 kg
- Net weight: .26 kg
- Length: 230 mm
- Width: 105 mm
- Height: 175 mm

Outer Carton
- EAN/UPC/GTIN: 87 10895 97659 6
- Quantity: 4
- Gross weight: 1.37 kg
- Tare weight: .85 kg
- Net weight: .52 kg
- Length: 250 mm
- Width: 235 mm
- Height: 195 mm

Packaging dimensions
- Packaging dimensions (W x H x D): 16.5 x 23 x 6 cm
- Nett weight: .13 kg
- Gross weight: .21 kg
- Tare weight: .08 kg

Outer Carton
- Outer carton (L x W x H): 25 x 23.5 x 19.5 cm
- Nett weight: .52 kg
- Gross weight: 1.37 kg
- Tare weight: .85 kg

Inner Carton
- Inner carton (L x W x H): 23 x 10.5 x 17.5 cm
- Nett weight: .26 kg
- Gross weight: .54 kg
- Tare weight: .28 kg

Product highlights

Digital signal transfer
High quality cable provides great signal transfer, using digital technology.

100% aluminum shielding
This protective layer of aluminum guards against electromagnetic interference for improved signal quality.

Copper braided shielding
This protective layer of copper blocks radio frequency interference for improved signal quality.

FPE Dielectric
Foam Polyethlene (FPE) dielectric is a superior insulation material that protects against signal loss.

Color-coded connectors
Color coded connections make it easy to install your cable into the correct inputs and outputs

Easy grip
This non-slip grip makes connecting your components easy and ergonomically comfortable.

Plug and play
Plug and play offers easy installation of components without time-consuming installations.

Heavy-duty brass shell
The heavy-duty brass shell protects the internal connection of the cable. It ensures durability and the reliability of your connection.

Super pliable jackets
Super pliable PVC jackets are abrasion-resistant for outstanding flexibility and protection against everyday wear and tear.

Metal strain relief
Full metal connector ensures extended durability by preventing damage during use and installation.

Twisted high purity OFC
This oxygen-free copper conductor provides the highest accuracy in signal transfer with minimal resistance.

Issue date 2008-09-02
Version: 7.0.9
12 NC: 9082 100 07579
EAN: 87 10895 95422 8

© 2008 Koninklijke Philips Electronics N.V.
All Rights reserved.
Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.

www.philips.com